



		Specifications
<b>Number of input points</b>		16 points
<b>Insulation method</b>		Photocoupler
<b>Rated Voltage</b>		5~125 VDC or 12~250 VAC (only 1 AC power source allowed per module)
<b>Rated Current</b>		Max. 2 A/pt., 8 A /common Min. 0.1 mA
<b>Insulation method response time</b>	<b>OFF→ON</b>	10 ms or less
	<b>ON→OFF</b>	5 ms or less
<b>Max. switching frequency</b>		3600 times per hour
<b>Common terminal arrangement</b>		8 points/ common
<b>External power supply</b>	<b>Voltage</b>	<b>Voltage:</b> 24 VDC±10%, <b>Ripple voltage:</b> 4V p-p or less
	<b>Current</b>	90 mA (24 VDC, all points ON)
<b>Service Life</b>	<b>Mechanical</b>	More than 20 million times
	<b>Electrical</b>	250 VAC/2 A, 30 VDC/2 A more than 100,000 times
<b>Internal current consumption</b>		100 mA (all points ON)
<b>Error Display LED</b>		LED goes ON when no external power
<b>Operating indicator LED's</b>		ON state is indicated
<b>External Connections</b>		20-pt. terminal block connector, max. wire size #14 AWG
<b>Weight</b>		310 g

